



**CALIFORNIA AIR TOOLS 20040DSPCADC Powerful 4.0 Hp Ultra Quiet & Oil-Free Air Compressor with 98% Air Drying System and Automatic Drain in a Soundproof Cabinet**

**20** Gallon

---

**4** HP Motor

---

**125** PSI MAX

---


**10.6** CFM @90PSI

---

**65** Decibels

---

**98%** Dry Air



Automatic Drain Valve

- 4.0 HP (Rated/Running)**
- 20 Gallon Steel Tank in a Soundproof Cabinet**
- Air Dryer Cartridge System - Up to 98% Dry Air**
- 12.80 CFM @ 40 PSI**
- 10.60 CFM @ 90 PSI**
- 220 Volts / 60 Hertz / Single Phase**


The CALIFORNIA AIR TOOLS 20040DSPCADC Ultra Quiet & Oil-Free Air Compressor with Air Drying System and Auto Drain in a Soundproof Cabinet is designed to be one of the quietest 4.0 horsepower air compressors in the industry having only 65 decibels of sound.

**65 Decibels**


Tank Pressure Gauge/  
Regulated Pressure Gauge/  
Output Pressure Gauge

**20 Gallon Air Tank with Auto Drain, Ultra Air Dryer, (2) 0.01um Prefilters and Aftercooler in Soundproof Cabinet**

**4 HP Oil-Free Dual-Piston Long-Life Motor Pump**



**375 lbs 220 Volts 14 Amps**



The Powerful Twin 2.0 HP (SP-9421-22060) motors operate at only 1680 RPM creating less noise and less wear.

**ULTRA QUIET**

**ONLY 65 DB NOISE LEVEL**

The Oil-Free Dual Piston Pump System is engineered for high performance and durability.

The CAT-20040DSPCADC Air Compressor has a Oil-Free Dual Piston pump designed to have a life cycle before wear of 3000 Plus hours.

The Oil-Free pump allows for use in a variety of temperatures (cold starts) and uneven terrains (no oil in the pump).

The large 20 Gallon Steel Air Tank is just the right size for a shop or garage.

**98% AIR DRYER SYSTEM**


To dry the air from the air compressor an Aftercooler and 98% Air Dryer are utilized.

The aftercooler is a heat exchanger for cooling the discharge air from the air compressor. The water vapor from the compressed air is condensed into liquid form and pushed into the Air Dryer.

The easy to replace "Spin-On" Air Dryer Cartridge has a regenerating High-Temperature Molecular Sieve Desiccant to dry the air.

This cartridge dryer has a life of 2-years before replacement.





## FEATURES

- \* **Ultra Quiet** - Only **65 decibels**
- \* **Oil-Free Pump (Class 1)** - Cleaner air for better tool operation.  
Less maintenance and Costs.
- \* **0.01 Micron Prefilters (2 total)**
- \* **5.0 Micron (Class 2) Air Filter Regulator**
- \* **Two pressure control gauges**
- \* **Two - Female industrial "Push to Connect" quick connectors**
- \* **Condor Pressure Switch**
- \* **Thermal Overload Protector**
- \* **130 PSI Maximum Pressure**
- \* **220 Volts / 60 Hertz / Single Phase** - (No 208 Volts - if necessary, obtain 208 to 220 voltage booster)
- \* **Low Amp Draw - 14 Amps**
- \* **Time to fill tank from empty to full - 150 Seconds**
- \* **Recovery time from 100 PSI to 130 PSI - 40 Seconds**
- \* **Duty Cycle - 70/30\***
- \* **20 Gal. Steel Air Tank**
- \* **L (31") x W/D (46") x H (39")**
- \* **375 lbs**
- \* **Non-ASME Air Tank**
- \* **Air Dryer Cartridge uses a High-Temperature Molecular Sieve Desiccant**  
Easy to remove (spin off) and replace every 2 years.
- \* **Aftercooler (condenser)**
- \* **PDP performance range (-20' F. to -51' F.)**
- \* **Air Quality: ISO 8573 - Class 2.3.1**
- \* **1 Year Limited Warranty**
- \* **Comes complete (4) Air Filters**
- \* **Plug Type: Nema 6-15P (fits Nema 6-15R or 6-20R receptacle)**
- \* **EZ-1-2321 Auto Drain Valve Factory Installed**
- \* **Commercial Use: Refer to State & City Codes**
- \* **Assembled in USA with global components**

For more information and to watch a 20040DSPCADC product demonstration please visit California Air Tools: <https://www.californiaairtools.com/air-dryer-ultra-quiet-oil-free-air-compressors/cat-20040dspcadc/>

*Manufactured in Mexico using global components.*  
MODEL: 20040DSPCADC  
PART NUMBER: CAT-20040DSPCADC  
[www.californiaairtools.com](http://www.californiaairtools.com)  
Revision A: 07-2024